



KERN FCB Compact model with large weighing plate at a low price

Delivery 1 day

2 Years warranty

Strain gauge

OPTION DKD Certificate +3 days

* while stocks last



Price reduction

CAL EXT Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required.

PCS Piece counting: Reference quantities selectable. Display can be switched from piece to weight.

PC IT-Net Data interface: The type of interface is shown by the pictogram. For a definition, see glossary.

REZ Net-total weighing: weight of tare cup and weight of components memorized in two separate stores.

% Percentage determination: Displays the deviation from the reference weight (100%) in % instead of grams.

UNIT Weighing units: can be switched to e.g. non-metric units at the touch of a key. See balance model.

Animal weighing program: strong vibrations are filtered out.

BAT Battery operation: The battery type is specified for each device.

230 Mains adapter: 230 V/50Hz in standard version for Germany. On request GB, AUS or USA version.

PRE-TARE function for manual subtraction of a known container weight

BAT **Battery operation possible**
Block battery (9V) not included

Backlit LCD display
digit height 25 mm



Second display on the rear of the balance

AKU **Rechargeable battery pack**
internal, KERN FCB-A01

Protective working cover over keypad, standard. Can be reordered, KERN FCB-A02

Standard printer, KERN YKB-01N

Label printer, with printout configuration and barcode function, KERN YKL-01

Statistics printer, KERN YKT-01

For all printers, see page 109. See also "Individual header data"

- STANDARD**
- CAL EXT
 - PCS
 - PC RS 232
 - REZ
 - %
 - UNIT
 - Animal weighing
 - BAT
 - 230
- OPTION**
- DKD

Technical Data:

Overall dimensions WxDxH 270x345x106 mm

Net weight approx. 3 kg

Permissible ambient temperature +5 ... +35 °C

UNITS Further weighing units: see the internet

Option (additional price)

AKU Rechargeable battery pack: rechargeable set.

Model	Weighing range	Read-out	Repro-ducibility	Linearity	Min. piece weight at piece count.	OPTION DKD Certificate KERN
KERN	Max kg	d g	g	g	g/piece	
FCB 3K0.1	3	0,1	0,1	± 0,3	0,2	963-127
FCB 8K0.1	8	0,1	0,1	± 0,3	0,2	963-128
FCB 16K0.2*	16	0,2	0,2	± 0,6	0,4	963-128
FCB 6K0.5	6	0,5	0,5	± 1,5	1	963-128
FCB 30K0.5*	30	0,5	0,5	± 1,5	1	963-128
FCB 12K1	12	1	1	± 3	2	963-128
FCB 30K1	30	1	1	± 3	2	963-128
FCB 24K2	24	2	2	± 6	4	963-128
FCB 15K5	15	5	5	± 10	10	963-128
FCB 24K10*	24	10	10	± 20	20	963-128



Intertech d.o.o.
VII. Ulica - Del 007
SI-1235 Radomlje, Slovenia EU

www.Tehtnice.net

TEL.: +386-1-7297-234
MOB.: +386-41-819-607